(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 19 February 2004 (19.02.2004)

PCT

(10) International Publication Number WO 2004/016035 A2

(51) International Patent Classification⁷:

H04R

(21) International Application Number:

PCT/IL2003/000660

- (22) International Filing Date: 7 August 2003 (07.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/402,241

8 August 2002 (08.08.2002) U

- (71) Applicant (for all designated States except US): CROW ELECTRONIC ENGINEERING LTD. [IL/IL]; 57 Hamelacha Street, 58855 Holon (IL).
- (72) Inventor; and

WO 2004/016035 A2


36,37

(75) Inventor/Applicant (for US only): MELMAN, Shmuel [IL/IL]; 64 Pinkas Street, Apartment 115, 62155 Tel Aviv (IL).

- (74) Agents: SANFORD T. COLB & CO. et al.; P.O. Box 2273, 76122 Rehovot (IL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PIEZOELECTRIC LOUDSPEAKER



(57) Abstract: A loudspeaker (8), including a piezoelectric disk (10) having a first diameter and a diaphragm disk (12) which is fixed to the piezoelectric disk. The diaphragm disk has a second diameter greater than the first diameter. The loudspeaker further includes a cover (14), consisting of a convex surface (24) bounded by an annulus (26,27), which mates with the diaphragm disk to form a generally plano-convex volume (28) between the diaphragm disk and the cover. A labyrinth (16, 18) is fixedly coupled to a circumference of the annulus to provide a path (34) for sound waves.